

All posters and product drawings are copyrighted by AutoBuff. Appearance and parameters are for reference only. Our company reserves the right of final interpretation. Information is subject to change without further notice.



ZHEJIANG GUANXIN TECHNOLOGY CO.,LTD.

Add: Jinyanshan Industry Zone, Quanxi Town, Wuyi County,
zhejiang Province, China

Mobile: 0086-15858957839 / 0086-18266937999

Tel: 0086-579-87720836 Fax: 0086-579-87720837

Email: gx@zjguanxin.com <https://www.auto-buff.com>

AUTO BUFF

2023 CATALOGUE

CAR CARE PROFESSIONALS

www.auto-buff.com

ZHEJIANG GUANXIN TECHNOLOGY CO., LTD.



CAR CARE PROFESSIONALS

About us:

AutoBuff is a fast-growing brand in the market of car care solutions with a strong focus on R&D and manufacturing excellence, striving to provide outstanding products to car care professionals around the globe.

History line:

Starting its first production in 2003, AutoBuff is producing a full range of corded, cordless car care power tools and professional accessories, including its lithium batteries in the hardware capital of China, Yangkang. The constant investment in new product development, quality, and manufacturing excellence allowed rapid growth in the company's product portfolio and global customer base. 2022 marked a milestone in the company's history with record sales and number of new products introduced.

Core Values and beliefs:

Our core values are the foundation of our company's success. Being present and following our values on every level in our organization is integral to our everyday interactions.

Core Values & Beliefs:

Exceeding customers expectations
Treating colleagues and customers with integrity and respect
Encourage innovation and excellence
Building strong and trusted relationships

Our Mission:

We are committed to developing and providing best-in-market solutions for car care professionals worldwide.

Quality:

Quality is at the core of our company's success.

From hiring, employee development, and product research to manufacturing and delivery, every level of our organization is included in a continuous improvement process. A holistic approach ensures superior quality and is part of the company's DNA.

Sustainability:

We take responsibility for our actions.

Complying with the legal requirements is a matter of course for us. Reducing the use of scarce resources, decreasing pollution, and focusing on minimizing the overall impact is an important goal to protect our environment and a competitive advantage that is gaining importance.



DUAL ACTION POLISHER

GX-CP04-15/125

GX-CP04-21/150



Dual Action



- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- Soft start function. Gentle start from a low speed can avoid the paintwork damages caused by sudden acceleration.
- 6 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.
- Carbon brush removable structure, convenient for users to replace the carbon brush.
- Orbit: 15mm/21mm

Model number: **GX-CP04-15/125** **GX-CP04-21/150**

Rated Voltage:	220V ~240V	220V ~240V
Rated Frequency:	50Hz / 60Hz	50Hz / 60Hz
Rated Input Power:	1050W	1050W
No load Speed:	1400-4800r/min	1400-4800r/min
Backing plate dia.:	5"(125mm)	6"(150mm)
Orbit:	15mm	21mm



6 Settings constant speed adjustment



Porous heat dissipation



Ergonomic design



FlexEdge with Hook and Loop



High-grade backing plate for options



Because of the deflected working principle of the dual action polisher, it requires for precise counterweight on backing plate and sponge pads in order to avoid abnormal vibrations, please use the original accessories to replace the wearing parts.

ROTARY POLISHER GX-CP08R



- It can be compatible with 25mm, 50mm and 75mm backing plate. It's flexible to change suitable size when working on different workplaces.
- Soft start function. Gentle start from a low speed can avoid avoid the paintwork damages caused by sudden acceleration.
- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- 6 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.



DUAL ACTION POLISHER GX-CP08A



- Constant speed function helps to avoid stalling under heavy load.
- Soft start function. Gentle start from a low speed can avoid avoid the paintwork damages caused by sudden acceleration.
- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- Orbit: 9mm



GX-CP08 DUAL ACTION POLISHER

- It can be compatible with 50mm and 75mm backing plate. It's flexible to change suitable size when working on different workplaces.
- Soft start function. Gentle start from a low speed can avoid avoid the paintwork damages caused by sudden acceleration.
- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- 6 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.
- Orbit: 7mm



Model number:	GX-CP08RO	GX-CP08A	GX-CP08
Rated Voltage:	220V -240V	220V -240V	220V -240V
Rated Frequency:	50Hz / 60Hz	50Hz / 60Hz	50Hz / 60Hz
Rated Input Power:	600W	600W	400W / 600W
No Load Speed:	1000-3500 r/min	2000-6800 r/min	2000-6800 r/min
Backing plate dia.:	1.2"(30mm) / 2"(50mm) / 3"(75mm)	5"(125mm)	2"(50mm) / 3"(75mm)
Orbit:	/	9mm	7mm



Because of the deflected working principle of the dual action polisher, it requires for precise counterweight on backing plate and sponge pads in order to avoid orbital vibration, please use the original accessories to replace the wearing parts.



INDUSTRIAL ROTARY POLISHER

GX-CP07



- Switch trigger with stepless speed regulation for better with better sensitivity on controlling the strength.
- The air inlet with filter mesh helps to effectively block dust or wax particles and protect the motor.
- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- Soft start function: Gentle start from a low speed can avoid avoids the paintwork damages caused by sudden acceleration.
- 7 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.
- Carbon brush removable structure, convenient for users to replace the carbon brush

Rated Voltage:	220V -240V
Rated Frequency:	50Hz / 60Hz
Rated Input Power:	1400W
Speed settings:	7 settings
Speed range:	0-600/0-1000/0-1400/0-1800/0-2200/0-2600/0-3000rpm
Backing plate dia.:	7" (180mm)



1. Suitable for complete vehicle or partial polishing.
2. No sponge and/or wool polishing bonnet larger than 7" (180mm) shall be used.
3. It is easy to cause heat or overheat when the machine is running at low speed. Cool machine down for a while.

CAR CARE PROFESSIONALS

- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- Soft start function: Gentle start from a low speed can avoid avoids the paintwork damages caused by sudden acceleration.
- 6 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.
- Carbon brush removable structure, convenient for users to replace the carbon brush
- Soft gripped switch with dustproof design
- The backing plate with reinforcing bars can better polish the work surface.



ROTARY POLISHER

GX-CP05D



Rated Voltage:	220V -240V
Rated Frequency:	50Hz / 60Hz
Rated Input Power:	1200W
No load Speed:	600-3500/min
Backing plate dia.:	6"(150mm)

- Soft start function: Gentle start from low speed can avoid the paintwork damages caused by sudden acceleration.
- 5 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.
- Quick access brush side ports
- Low noise and quiet polishing
- One-click to low speed



**AUTO
BUFF**

ROTARY POLISHER

GX-CP05P



Rated Voltage:	220V -240V
Rated Frequency:	50Hz / 60Hz
Rated Input Power:	1200W
No load Speed:	500-3500/min
Backing plate dia.:	6"(150mm)



- The two-stage reduction gear box increases the torque of the machine and improves the polishing efficiency.
- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- Soft start function: Gentle start from a low speed can avoid avoids the paintwork damages caused by sudden acceleration.
- 6 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.
- Carbon brush removable structure, convenient for users to replace the carbon brush
- Soft gripped switch with dustproof design
- The backing plate with reinforcing bars can better polish the work surface.



ROTARY POLISHER

GX-CP10



Rated Voltage:	220V -240V
Rated Frequency:	50Hz / 60Hz
Rated Input Power:	900W
No load Speed:	600-2200/min
Backing plate dia.:	6"(150mm) / 7"(180mm)



CAR CARE PROFESSIONALS

CORDLESS DUAL ACTION POLISHER GX-LCP01

- Brushless motor with greater efficiency and a longer service life.
- The battery pack is inserted horizontally to avoid friction with the working surface.
- Stepless speed control with trigger for better sensitivity on controlling the strength.
- The air inlet with filter mesh helps to effectively block dust or wax particles and protect the motor.
- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- Soft start function. Gentle start from a low speed can avoid avoids the paintwork damages caused by sudden acceleration.
- 7 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.
- Lockable switch for easy continuous operation. On the other hand, it's also a dual-start switch prevents the machine from being turned on accidentally.
- Orbit: 15mm / 21mm

Battery Voltage:	20V
No load speed:	2000-5000rpm
Max. backing plate dia.:	6" (125mm)
Max. polishing pad dia.:	6" (150mm)
Orbit:	15mm / 21mm
7 settings speed:	400-2000rpm/400-2500rpm 400-3000rpm/400-3500rpm/400-4000rpm/400-4500rpm/400-5000rpm



Dual Action

Voltage: 100-240V 50/60Hz
Output: 21.5V 4.5A
with battery charging indicator

20V 5.0Ah
Lithium battery pack



7 levels of constant speed setting



Stepless speed control trigger

CORDLESS 3 IN 1 SMART POLIHER QUICK SWITCHOVER

RANDOM ORBITAL
ROTARY / SANDER



Rotary Dual Action Sander

Max. backing plate dia.:	3" (75mm)
Max. polishing pad dia.:	3.2" (80mm)
Orbit:	3 + 12 mm
No load speed:	400-2000/3000/4000/5800 rpm
Battery voltage:	12V
Battery capacity:	2.5/5.0Ah



GX-LCP03

- Tools free to switchover the drive types of rotary and random orbital.
- 3mm and 12mm deflection distance can be reached on demand.
- ONE TOOL, ONLY 1 from sanding to polishing.
- Brushless motor with greater efficiency and a longer service life.
- Stepless speed control with trigger for better sensitivity on controlling the strength.
- Soft start function. Gentle start from a low speed can avoid avoids the paintwork caused by sudden acceleration.
- Lockable switch for easy continuous operation. On the other hand, it's also a dual-start switch prevents the machine from being turned on accidentally.
- 4 levels of constant speed setting helps better on controlling accurate speed, and does better to reach professional polishing demand.



Tool-free quick-change system



4 levels of constant speed setting



Voltage: 100-240V 50/60Hz
Output: 12V 2.5A
with battery charging indicator

12V 2.5Ah
Lithium battery pack

CORDLESS DUAL ACTION WAXER GX-LCP04

- 4 poles motor, small size and large strength
- Compact body at the same time accord with artificial mechanics, comfortable control
- Waterproof design at the switch to avoid switch failure caused by water
- 6 settings speed adjustment, to meet the needs of professional waxing and polishing
- Orbit: 8mm

Battery Voltage:	20V
No load speed:	3000-5500r/min
Backing plate dia.:	6" (150mm)
Orbit:	8mm



Voltage: 100-240V 50/60Hz
Output: 13V 2.0A
with battery charging indicator

12V 2.0Ah / 2.5Ah
Lithium battery pack



Fan self-cooling system



6 Settings constant speed adjustment

CORDLESS DUAL ACTION WAXER GX-LCP02



Battery Voltage:	12V
No load speed:	2200-5000r/min
Backing plate dia.:	6" (150mm)
Orbit:	8mm



- 4 poles motor, small size and large strength
- Compact body at the same time accord with artificial mechanics, comfortable control
- Waterproof design at the switch to avoid switch failure caused by water
- 6 settings speed adjustment, to meet the needs of professional waxing and polishing
- Orbit: 8mm



Voltage: 100-240V 50/60Hz
Output: 13V 2.0A
with battery charging indicator

12V 2.0Ah
Lithium battery pack



6 Settings constant speed adjustment



Waterproof switch

RANDOM ORBIT POLISHER GX-CP02

- Electronic module maintains specified speed even under load
- Conveniently-located variable speed dial lets user set maximum
- Speed from 2000 to 6400 for different materials and applications
- Heat-treated, precision-cut gears for smooth operation
- With soft start function, more gentle start, avoid accidental damage to car paint
- Orbit: 9mm

Rated Voltage:	220V -240V
Rated Frequency:	50Hz / 60Hz
Rated Input Power:	800W
No load Speed:	2000-6400r/min
Backing plate dia.:	6" (150mm)
Orbit:	9mm



6 Settings constant speed adjustment



Classic US style



RANDOM ORBIT POLISHER GX-CP09

- Constant speed function helps to avoid stalling under heavy load.
- Soft start function. Gentle start from a low speed can avoid the paintwork damages caused by sudden acceleration.
- The gearbox is surrounded by plastic cover, which is more convenient for consumers to control and hold, and to avoid heat sensation by direct contact.
- Detachable cord makes tool storage a snap.
- Quick access brush side ports



Rated Voltage:	220V-240V
Rated Frequency:	50Hz/60Hz
Rated Input Power:	900W
No load Speed:	2000-6500r/min
Backing plate dia.:	5" (125mm) / 6" (150mm)
Orbit:	9mm



Quick access brush side ports



Detachable cord



RANDOM ORBIT POLISHER GX-CP06

- The head shell is covered with plastic cover, which is more convenient for users to control and hold, and avoid hot feeling when hands touch the head shell
- With soft start function, more gentle start, avoid accidental damage to car paint
- 6 settings constant speed adjustment, more accurate control of speed, to meet the needs of professional polishers
- Carbon brush removable structure, convenient for users to replace the carbon brush
- Switch with soft grip and dustproof design
- Backing plate with reinforcing ribs, ensure the fitness of the working surface
- FFU durability good grade, no load time over 50 hours*



Rated Voltage:	220V-240V
Rated Frequency:	50Hz/60Hz
Rated Input Power:	650W
No load Speed:	2000-6800/min
Backing plate dia.:	5" (125mm)
Orbit:	9mm



Rated Voltage:	220V-240V
Rated Frequency:	50Hz/60Hz
Rated Input Power:	1200W
No load Speed:	800-3500/min
Backing plate dia.:	6" (150mm) / 7" (180mm)



ROTARY POLISHER GX-CP01

- With soft start function, more gentle start, avoid accidental damage to car paint



ROTARY POLISHER GX-CP11

- Low noise and quiet polishing
- Humanized switch design



Rated Voltage:	220V-240V
Rated Frequency:	50Hz/60Hz
Rated Input Power:	600W
No load Speed:	0-2800/min
Disc dia.:	5" (125mm)



CORDLESS 3 IN 1 SANDER GX-LMS01



Voltage: 100-240V 50/60Hz
Output: 13V 2.4A
with battery charging indicator

12V 2.0Ah / 2.5Ah
Lithium battery pack



- Ergonomic handles with non-slip soft grip equipment
- Velcro fastener makes it easy to change the sanding sheet
- Connection for external dust extraction - including adapter
- Suitable for standard sandpaper with Ø 125 mm
- Variable speed
- Compact design with soft grip handle
- Dust collection

Battery Voltage:	20V
No load speed:	3000-12000rpm
Backing plate dia.:	Ø 5" (125mm)/180x93mm/150x93mm



CORDLESS IMPACT WRENCH GX-BW01

- Brushless motor
- Powerful impact wrench for car wheel assembly
- Infinitely controllable beat/speed
- Integrated LED work light
- Square adapter: 1/2"
- Left/right rotation
- Ergonomic design with non-slip soft grip and practical belt clip



Battery Voltage:	20V
Maximum torque:	320N.m
Idle speed:	0-2000rpm



Voltage: 100-240V 50/60Hz
Output: 13V 4.5A
with battery charging indicator

20V 4.0Ah
Lithium battery pack

CORDLESS IMPACT WRENCH GX-BW03

- Brushless motor
- Powerful impact wrench for car wheel assembly
- Infinitely controllable beat/speed
- Integrated LED work light
- Square adapter: 1/2"
- Left/right rotation
- Ergonomic design with non-slip soft grip and practical belt clip



Battery Voltage:	20V
Maximum torque:	600N.m
Idle speed:	0-2200rpm



Voltage: 100-240V 50/60Hz
Output: 13V 4.5A
with battery charging indicator

20V 4.0Ah
Lithium battery pack

CORDLESS WATER GUN GX-LWG02

- Brushless motor
- Large diameter plunger pump
- Quick plug connector
- Fine filter screen
- 1 pc water pipe, 1 pc watering can, 1 pc filter, 1 pc 6in1 nozzle

Battery Voltage:	20V
No load speed:	4500r/min
Flow rate:	6-8L/min
Shooting distance:	around 12m



Voltage: 100-240V 50/60Hz
Output: 13V 4.5A
with battery charging indicator



20V 4.0Ah
Lithium battery pack



CORDLESS HANDHELD INFLATOR GX-LHI01

- Inflates a flat to full line in under 4 minutes
- Digital LCD display for enhanced accuracy within 1 PSI
- Automatic fill until pressure is reached
- Nozzle accessories and on-board storage included for a variety of inflation needs
- Inflates tires, sports equipment and other small inflatable

Battery Voltage:	20V
Operating air pressure:	10Bar
Inflation efficiency:	4min(0-2.5Bar)



Voltage: 100-240V 50/60Hz
Output: 13V 2.5A
with battery charging indicator



12V 2.0Ah / 2.5Ah
Lithium battery pack



Digital LCD display

HEAT GUN GX-HG01

- Stronger air supply from turbofan
- Anti scald design
- Intelligent temperature control
- Multi purpose adapter

Rated Voltage:	220V-240V
Rated Frequency:	50Hz/60Hz
Rated input power:	2000W
Temperature range:	100-650°C



7 levels of temperature setting





WOOL PAD

Striped short-nap cutting

- 100% fine wool pad with increased finishing performance.
- Remove 1200/1500# sanding disc marks, deep scratches, overspray, and heavy oxidation.
- Fast cutting for a smooth and glossy finishing.
- Recommended for DA/RO/GA polisher using.*

CUT
T140



MICRO-FIBER PAD

Finishing

- 100% Nano Micro-fiber.
- Increased finishing performance.
- Work as final step for a deep clear & perfect finishing.
- Recommended for DA/GA polisher using.

CUT
T20



GRIDDING FOAM POLISHING PAD

- Reduce polish splash, reduce heat build-up
- Reduce vibration and offer smoother handling
- Withstand high temperature and water wash
- Perfectly work with DA/RO/GA polisher



Green-Cutting

Green **T120** heavy cut foam is in solid construction, it fast removes the deep scratches, over spray, 1200/1500# sanding disc marks, and heavy oxidation. Cut like wool pad and leave high gloss finish. Applicable for scratch resistant and high solid ceramic paints.

CUT
T120



Orange-Correcting

Orange **T80** high cut foam has an intensive cutting action that will remove deep scratches, over spray, severe swirl marks, 1500# sanding disc marks, and heavy oxidation when used in conjunction with heavy polishing compounds.

CUT
T80



Yellow-Perfecting

Yellow **T60** foam has moderate cutting action that will remove 1500/2000# sand scratches, over spray, and surface imperfections when used in conjunction with polishing compounds.

CUT
T60



Blue-Protecting

Blue **T40** foam is universal and multi-purpose, it has a light cutting action, and will remove scratches and swirl marks while leaving a level and smooth surface, can be used in conjunction with polishing compounds or micro-fine compounds

CUT
T40



Red-Waxing

Red **T10** foam has very light cleaning action for removal of ultra-fine swirl marks, car wash scratches, and hazing, leaving a swirl-free gloss finish when used in conjunction with finishing polishes.

CUT
T10

