

Thyristor Modules

1 / 2

TYPE: YZPST-PWA150SA-400

This product is a Thyristor module suitable for low voltage, 3 phase rectifier applications.

- IT(AV) 150A (each device)
- High Surge Current 3000 A (60Hz)
- Easy Construction
- Non-isolated. Mounting base as common Anode terminal

Applications

- Welding power Supply
- Various DC power Supply

Maximum Ratings

Symbol	Condition	Ratings	Unit
$I_{T(AV)}$	Single phase, half wave, 180° conduction, $T_C=116^\circ\text{C}$	150	A
I_{TRMS}	Single phase, half wave, 180° conduction, $T_C=116^\circ\text{C}$	230	A
I_{TSM}	$T_J=150^\circ\text{C}$	3000	A
I^2t	$T_J=150^\circ\text{C}$	38	kA^2S
V_{DRM}/V_{RRM}		400/400	V
di/dt	non-repetitive	100	A/us
V_{iso}	A.C. 1 minute	3000	V
T_J		-30 ~ +150	$^\circ\text{C}$
T_{stg}		-30 ~ +125	$^\circ\text{C}$
W	approximate	250	g

Electrical Characteristics

Symbol	Condition	Ratings	Unit
I_{DRM} / I_{RRM}	At V_{DRM} , Single phase, half wave, $T_J=150^\circ\text{C}$	40	mA
V_{TM}	On-State Current 450A, $T_J=150^\circ\text{C}$	1.2	V
$V_{T(TO)}$	$T_J=150^\circ\text{C}$	-	V
t_{gd}	$T_J=25^\circ\text{C}$	-	us
t_q	$T_J=150^\circ\text{C}$	-	us
I_{GT}/V_{GT}	$T_J=25^\circ\text{C}$	100 / 3.0	mA/V
V_{GD}	$V_D=67\%V_{DRM}$, $T_J=150^\circ\text{C}$	0.25	V
DV/DT	$V_D=67\%V_{DRM}$	200	V/us
I_H	$T_J=25^\circ\text{C}$	-	mA
I_L	$T_J=25^\circ\text{C}$	-	mA
$R_{th(j-c)}$	Per Module	0.15	$^\circ\text{C/W}$



®

Tel: +86-514-87782298, 87782296 FAX: +86-514-87782297, 87367519
 E-mail: positioning@china.com; info@yzpst.com; info@stt.tm; info@goldstar.tm
 Web Site: www.pst888.com www.stt.tm www.goldstar.tm
www.positioning.en.alibaba.com www.pst.manufacturer.globalsources.com

Thyristor Modules

2 / 2

TYPE:YZPST-PWA150SA-400

Outline Drawing

