



www.friggatech.com

## B92(2G) Real-time Monitor (Multi use + Rechargeable)

## Temperature, Humidity, Weak Light, Shock, Location

R	Global real-time temperature monitor	FRIGGA <sup>®</sup> Real Time Cold Chain Solutions
LSB	Data is stored in the cloud for traceability; USB port for backup PDF data download	B9 IIII Device ID: F00R0000
9	Full cold chain visibility(Location, Temperature, Humidity, Light, Shock, Route) via Frigga cloud	Mattery oc     Mattery iss     Mattery iss     Mattery oc     Mattery Status       Significant oc     Mattery iss     Mattery iss     Mattery Status     Mattery Status       Precedence oc     Mattery iss     Mattery iss     Mattery iss     Mattery iss
	Improve transportation efficiency and reduce products loss with real-time monitoring	Real-time
	24/7 data control & analysis, manage quality and control of your products in-transit. Real time alert via SMS, Email and APP	
C	Support weak light detection, protect the safety of your goods effectively	

## **SPECIFICATIONS**

Configure	Parameters
Usage Type	Multi use(Reusable)+Rechargeable
Monitor Information	Temperature, Humidity, Light , Shock, Location, Track routes
Temperature Sensor	Internal Texas Instruments (TI) Brand Digital Sensor
Temperature Measurement Range	-30°C ~ 70°C ( -22°F ~ 158°F)
Temperature Accuracy Range	±0.5°C (-20°C ~ +40°C); ±1°C for other range
Humidity Measurement Range	5%~95%RH
Humidity Accuracy Range	±3%(20%~80%RH); ±5% for other range
Resolution(Temperature/Humidity)	0.1°C / 1%RH
Light Sensor Range	0~1700 Lux, detect whether doors or cartons open
Memory Capacity	Max 28800 readings
Location Type	LBS Base Station Positioning
Cellular	2G network.
SIM Card	Internal Embedded (Global Data Roaming)
Shelf Time	12 Months
Use Time	120 days use time for 1 charge with 120 reporting interval
Data Logging Interval	10 Min. (settable via platform)
Data Reporting Interval	10 Min. (10/20/30/60/120 Min settable via platform)
Environmental Rating	IP64
Cold Chain PDF Report	Get PDF report via USB2.0/ Frigga cloud platform/Frigga Track(Mobile App)
Dimensions/Weight	102 x 59 x 19 mm / 140 grams
Certifications	FCC,CE,RTCA/DO-160G,UN38.3,ROHS,WEEE
Storage temperature range	-10°C ~ +55°C



る
る
る
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ
ろ

www.friggatech.com