



● Dual Temperature

● Weak Light







● Location

V5Y(4G-60) Real-time Monitor (Single-use)



V5Y(4G-60) Real-time Monitor (Single-use)

Dual Temperature, Weak Light, Location

-  New generation of global real-time temperature monitor
-  Data is stored in the cloud for traceability; USB port for backup PDF data download
-  Full cold chain visibility(Location, Dual temperature, Light, Route) via Frigga cloud
-  Improve transportation efficiency and reduce products loss with real-time monitoring
-  24/7 data control & analysis, manage quality and control of your products in-transit. Real time alert via SMS, Email and APP
-  Support weak light detection, protect the safety of your goods effectively



SPECIFICATIONS

Configure	Parameters
Usage Type	Single-use(Max 60days)
Monitor Information	Dual Temperature, Light , Location, Track routes
Temperature Sensor	External + Internal Dual Digital Temperature Sensors
Temperature Measurement Range	External : -40°C ~ 80°C (-40°F ~ 176°F) Internal : -30°C ~ 70°C (-22°F ~ 158°F)
Temperature Accuracy Range	±0.5°C (-20°C ~ +40°C); ±1°C for other range
Resolution	0.1°C
Light Sensor Range	0~52,000 Lux, detect whether doors or cartons open
Memory Capacity	Max 28800 readings
Location Type	LBS Base Station Positioning
Cellular	Global LTE 4G/5G, fallback 2G network.
SIM Card	Internal Embedded (Global Data Roaming)
Shelf Time	12 Months
Use Time	60 Days use time with 60 Min reporting interval
Data Logging Interval	10 Min. (settable via platform)
Data Reporting Interval	10 Min. (10/20/30/60 Min settable via platform)
Environmental Rating	IP64
Cold Chain PDF Report	Get PDF report via USB2.0/ Frigga cloud platform/Frigga Track(Mobile App)
Dimensions/Weight	103 x 61.3 x 23 mm / 250 grams
Certifications	FCC,CE,RTCA/DO-160G,UN38.3,ROHS,WEEE
Storage temperature range	-10°C ~ +55°C