

MODEL : GB-30

HYBRID POWER STATION



Design Standards

GB® is a new range of secure integrated hybrid power station. With diesel generator, Battery storage and Hybrid solar Inverter in one secure unit for option.

GB® is mainly developed for lower emission, Reduce the dependence on Main Power and decrease the consumption cost.

Benefits

- Integrated installation, convenient storage and transportation;
 - High return on investment and quick return;
 - Simple operation and easy maintenance;
 - Power and Capacity can be expanded, meet different user needs;
- Accept customer customization, suitable for various scenarios;


Warranty

- Battery Performance: 2000 cycles(80% DOD) or 2 years after manufacture;
- Generator: 18 months after manufacture or 1500 hours running time;



General Specification

Model	GB-30
System Rated Output Power	30 kVA
Rated Output Voltage	400V/230V@50Hz/60Hz,3ph. (According to customer requirements)
Min.Battery Storage Capacity	40 kWh
Max.Battery Storage Capacity	60 kWh
Output Terminals	Copper terminals & CEE 63A/5P Socket
Loading Dimension(W*D*H)	2450*1150*2150mm
Net.Weight	2250kg
Loading Capacity of 40'HC	8 units
Discharge Temperature Range	-20°C~50°C



GENERATOR
RATED POWER: 16kW
With **LOW CONSUMPTION**
DOWN TO **5.3 L/H~!!**



HIGH STRENGTH
METAL FRAME

COFFIDENCE IN
FACING **WIND & RAIN**
& **SNOW**



INTELLIGENT PCS
with **EMS**

EASY OPERATION ON
ONE SCREEN

Fits the practical
application & guaranteed
by high-quality
manufacturing
technology



Generator Set

Prime Power	20 kVA/16 kW
Rated Voltage	400V@50HZ
Engine to Ref.	404D-22G(Perkins)
Emission	EU Stage IIIA
Fuel Consumption	5.3 L/h@100% load
Fuel Type	Diesel(Nature Gas Engine for option)
Fuel Tank Capacity	12 hours
Base Functions	Automatic Start-up / Alarm / Automatic Stop / Emergency Stop / Load Management

Energy storage battery

Cell Type	LFP(LiFePO4)
Pack Model	MF51100
Pack Capacity	5 kWh
Pack Rated Voltage	51.2 VDC
Discharge Depth	90%
Charger/Discharge Current	97.7 A(1.0C)
Battery Rack Voltage	345.6V~708V
Rated Cycle Life	≥2000 (80% DOD)

Power Conversion System

EMS	ASC 150(DEIF)
AC Voltage Range	400Vac(480V@60HZ)
Max.Charge/Discharge Current	90A
Max.Conversion Efficiency	97.6%
Rated Output Power	30kVA(0.8leading~0.8lagging)
Certification	IEC 62109;IEC 61000;EN 50549;AS 4777.2;VDE4105;IEEE 1547;UL 1741

DC/DC Converter-OPTIONAL


Solar Controller	MPPT*6
Max.PV Input Power	45000W

Options

Engine	Alternator	Fuel System	Hybrid Power Station
Water Jacket Preheater Oil Preheater Oil manual pump	PMG excitation Space heater Winding temperature measuring	12 / 24 hour base tank Bunded fuel tank External fuel tank Automatic fuel feeding Switch between external tank and base tank (three-way valve)	Deepsea, ComAp, Smartgen etc. controller Tools with the machine

MPMC BEYOND ENERGY

Basic Logic



Power Priority	Highest	Secondary	Back Up
Functions	PV (Optional) Take load/charge	Battery Take load	Generator Take load/charge



MPMC POWERTECH CORP.
sales@mpmc-china.com | www.mpmc-china.com

Photographs are for illustrative purposes only and may not reflect final specification.

Follow us

- <https://www.facebook.com/mpmcgroup>
- <https://www.linkedin.com/company/mpmcpowertech/>
- <https://www.youtube.com/user/MPMCGenerator>

All information in this document is substantially correct at time of printing and may be altered subsequently. Final weight and dimensions will depend on completed specification.