


MLT4KD-2000LS-1

Powered by Kubota


8U. / 40 'HC. CONTAINER




✓ Highlights

-  Less fuel consumption. Longer run-time
-  Simple control system
-  High efficiency
-  Sturdy and durable
-  Max height 9.5m





50m / 159Lx



100m / 38Lx



150m / 16Lx

Lighting Tower Technical Data

Power Package Rated Power	5.17kW
Number & Power of Lamp	4×500W
Rated Frequency / Speed	50Hz /1500 rpm
Rated Voltage	AC 230V
Noise	73dB(A) @7M
Mast-Maximum Height	9.5m
Mast Lifting & Extension	Hydraulic Operation
Fuel level gauge	Electronic
Tower leg type	Manual
AUX. Power output	16A/3P Socket
Rotation angle range of light	355°
Wind resistance grade	100km/h
Recommended use environment	Level ground

Lamp

Number×Power	4×500W
Lamp type	LED
Protection Glass	IP54
Luminous Efficiency	170 lm/W
Color Temperature	5700±300 K
Voltage	AC 230V
Lamp Service Life	50000hrs


Control System

Controller Model	MALC404
------------------	---------

Dimension and Weight

Max Overall Dimension(L×W×H)	2278x2364x9500mm
Container loading Dimension (L×W×H)	2278x1564x2463mm
Tank Capacity / Running Hr.	100L / 112hrs.
Weight	1350kg
The loading capacity(40'HC)	8 sets

Note: Specifications and illustrations are subject to revision without notice.



Environmental Conditions

- Ambient temperature: +5℃~40℃
- Altitude: ≤1000m

Note: Please contact us if operating environmental conditions required do not go with the guidance.

Factory Inspection

- Complete design and quality inspection
- 30 mins full load test
- Function testing
- Protection testing

Painting Process

- MPMC has the most advanced automatic spraying / powder coating production line, and is equipped with various sandblasting equipment to ensure higher quality.
- Canopy painting: HenKel pretreatment process and world famous brand AkzoNobel powder.
- Base Frame painting: Sandblasting process and AkzoNobel powder(Hempel paint is optional).



ISO9001:2005
System certified



ISO9001:2005
System certified



ISO45001
System certified



ISO9001:2005
System certified

Engine Specifications

Engine Model	Z482-ET03
Manufacturer	Kubota
Emission	Tier 3
Number of Cylinders	2
Cycle	4 Stroke
Aspiration	Naturally
Prime Power / Speed (Gross)	6.9kW / 3000rpm
Lube-oil Capability	2.5L
Fuel consumption	0.89L/h (@100% Brightness)
Starter motor/ Alternator	12V 0.8kW

- Heavy duty diesel engine
- Anti-vibration mount
- Replaceable fuel filter, oil filter & air filter
- Cooling radiator and fan
- Starter battery (with lead acid) including rack and cables
- Flexible fuel connection hoses
- Exhaust silencer and bellows
- Operation manuals and circuit diagram document

Alternator Specifications

Alternator Model	KT06-2
Manufacturer	DGOL
Rated Output Power	6kW
Alternator Type	Brushless
Rated Voltage	AC 230V
Rated Speed	3000 RPM
IP Protection	IP21
Insulation Grade	H

OPTIONS

☐ Jacket water heater	☐ Manual pump
☐ Lub-oil heater	☐ Smartgen controller
☐ ABB/Schneider MCB	☐ Sockets
☐ Battery charger	☐ Larger fuel tank



MPMC POWERTECH CORP.

sales@mpmc-china.com | www.mpmc-china.com

Photographs are for illustrative purposes only and may not reflect final configuration.

Follow us



<https://www.facebook.com/mpmcgroup>



<https://www.linkedin.com/company/mpmcpowertech/>



<https://www.youtube.com/user/MPMCGenerator>

All information in this document is substantially correct at time of printing and may be altered subsequently. Final weight and dimensions will depend on completed specification.