MPMC BEYOND ENERGY

MLT4KME-1400LD-1

Powered by Kubota

16 unit / 40 'HC. CONTAINER





Highlights

- Less fuel consumption. Longer run-time
- Simple control system
- High efficiency
- Sturdy and durable
- Max height 7.2m

MPMC BEYOND ENERGY







Lighting Tower Technical Data	
Power Package Rated Power	2.5kW
Number & Power of Lamp	4×350W
Rated Frequency / Speed	50Hz /1500 rpm
Rated Voltage	AC 230V
Noise	63dB(A) @7M
Mast-Maximum Height	7.2m
Mast Lifting & Extension	Manual Operation
Tower leg type	Manual
Trailer Load bearing	750kg
Trailer type	Off road type
AUX. Power output	16A/3P Socket
Rotation angle range of light	355°
Wind resistance grade	100km/h
Recommended use environment	Level ground
Lamp	
Number×Power	4×350W
Lamp type	LED
Protection Glass	IP67
Luminous Efficiency	170Lm/W
Color Temperature	5700 K
Voltage	AC 230V
Lamp Service Life	50000hrs
Control System	
Controller Model	MALC404
Dimension and Weight	
Max Overall Dimension(L×W×H)	3080 * 2310*7200mm
Container loading Dimension (L×W×H)	1473 * 1100 * 2502mm
Tank Capacity / Running Hr.	100L / 175hrs.
Weight	700kg
The loading capacity(40'HC)	16 sets

Note: Specifications and illustrations are subject to revision without notice.



Environmental Conditions

- Ambient temperature: ＋5℃~40℃
- Altitude: ≤1000m

Note: Please contact us if operating environmental conditions required do not go with the guidance.

Factory Inspection

- Complete design and quality inspection
- 30 mins full load test
- Function testing
- Protection testing

Painting Process

- MPMC has the most advanced automatic spraying / powder coating production line, and is equipped with various sandblasting equipment to ensure higher quality.
- Canopy painting: HenKel pretreatment process and world famous brand AkzoNobel powder.
- Base Frame painting: Sandblasting process and AkzoNobel powder(Hempel paint is optional).

LABORATORY ACCREDITATION CERTIFICATE

Certificate of the World Manufacturer Identifier Code

MPMC BEYOND ENERGY

Engine Specifications

Engine Model	Z482-B-CHN-1
Manufacturer	Kubota
Emission	NA
Number of Cylinders	2
Cycle	4 Stroke
Aspiration	Naturally
Net Continuous power / Speed (Gross)	3.4 kW / 1500RPM
Lube-oil Capability	2.5L
Fuel consumption	0.57 L/h (@100% Brightness)
Starter motor/ Alternator	12V 0.95kW

- Heavy duty diesel engine
- Anti-vibration mount
- Replaceable fuel filter, oil filter & air filter
- Cooling radiator and fan
- Starter battery (with lead acid) including rack and cables
- Flexible fuel connection hoses
- Exhaust silencer and bellows
- Operation manuals and circuit diagram document

Alternator Specifications

Alternator Model	LT3N-75/4
Manufacturer	MECC
Rated Output Power	3.5kVA
Alternator Type	Brushless
Rated Voltage	AC 230V
Rated Speed	1500 rpm
IP Protection	IP23
Insulation Grade	H

OPTIONS

☐ Jacket water heater	☐ Manual pump
☐ Lub-oil heater	☐ Smartgen controller
☐ ABB/Schneider MCB	☐ Sockets
☐ Battery charger	☐ Larger fuel tank

MPMC BEYOND ENERGY

MPMC USA MPMC CN

MPMC POWERTECH CORP.
sales@mpmc-china.com | www.mpmc-china.com

Photographs are for illustrative purposes only and may not reflect final configuration.

Follow us

https://www.facebook.com/mpmcgroup
https://www.linkedin.com/company/mpmcpowertech/
https://www.youtube.com/user/MPMCGenerator

All information in this document is substantially correct at time of printing and may be altered subsequently. Final weight and dimensions will depend on completed specification.

MPMC BEYOND ENERGY

ISSUE 1 @ MPMC EN