

DBS50

ACCESSORIES

	
DBS50 Controller	DBS50 Motor
	
DBS50 Idle Pulley	DBS50 Hangers
	
DBS50 Power Cable	DBS50 Belt Bracket
	
DBS50 Cable Holder	DBS50 Fixed Plate
	
DBS50 Remote Control	DBS50 Stopper
	
Belt	Microwave Sensor

TECHNICAL DATA

Door form: single door / double door
 Loading weight: $\leq 2 \times 150\text{kg}$ / $\leq 4 \times 100\text{kg}$
 Clean opening width: 1200-2700mm/2200-3900mm
 Power supply: AC 110~220V $\pm 10\%$, 50/60Hz
 Power consumption: <150W
 Opening speed: 300-550mm/S (adjustable)
 Closing speed: 200-500mm/S (adjustable)
 Open time: 1-20S (adjustable)
 Closed force F:>100N
 Manual force: <100N
 Humidity range: -20 ~ +50°C

FEATURES

The controller has a built-in chip that can be intelligently adjusted to realize the automatic setting control process. The parameters can be flexibly set as needed to maintain optimal operation.

Two kinds of high-strength aluminum alloy guide rails are combined and connected with special accessories, which are easy to install and overall firm and beautiful. The overlapping door bodies are interlocked by the pulleys, and the operation is stable and reliable.

A high-quality EPDM strip is embedded in the middle of the rail slide section to absorb vibration and noise during operation, and the automatic door runs quieter.

Two-way resistance automatic rebound function, safety performance is more prominent.

It is applicable to airports, hospitals, office buildings, stations, banks, factories, hotels, shopping centers, hotels, office buildings, financial and financial institutions, companies and high-end residential and other places require big clean opening.

SECTIONAL VIEW

